Orchard Herbicide



MODEL SPECIFICATIONS

| PUMP | Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. BP125/20: 121L/min. capacity 2000 kPa pressure |
|----------|---|
| CONTROLS | 3 section electric valve on/off with electric pressure adjustment from cab mounted control box. |
| TANK | Polytuff impact resistant polyethylene construction, calibrated sight line. |
| В00М | 6 metre fully galvanised hydraulic fold boom with stainless steel spraylines and air induction nozzles. Front mounted boom arms with independent hydraulic fold and rear mounted centre boom. |

| FRAME | Galvanised RHS heavy duty steel construction, jockey wheel and adjustable tow hitch. | | | | | |
|-----------------------------|--|--------|--------|----------|--|--|
| AGITATION | Bypass action. | | | | | |
| PRESSURE GAUGE | 0-25 Bar dual stage glycerine filled gauge. | | | | | |
| FILTRATION | Lid strainer, suction line strainer & nozzle strainers. | | | | | |
| WHEEL EQUIPMENT | Single axle with 31/13.5 x 15" flotation tyres. | | | | | |
| PTO DRIVESHAFT | Quality driveshaft with quick release pins & safety cover. | | | | | |
| DIMENSIONS (BOOM FOLDED) | L (MM) | W (MM) | н (мм) | KG (DRY) | | |
| JB2BA-125 | 3500 | 1550 | 2100 | 440 | | |

| MODEL DESCRIPTION | CODE | |
|--|---------|--|
| 2000L TRAILED ORCHARD HERBICIDE SPRAYER: BP125/20 Pump and hydraulic fold boom | | |
| FACTORY FITTED OPTIONS | CODE | |
| Bravo 180S automatic spray rate controller | J99-146 | |
| Hydraulic drive centrifugal pump | J99-126 | |
| When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be on order. Note: Extra charges may apply to fitment of some options. | | |

