


# 3000L TGS Vineyard Sprayer



OPTIONAL OVERSIZE ROAD KIT WITH 12V TAIL LIGHTS & INDICATORS



Pictured: 2 Row 3000L TGS with optional twin galvanised snorkel

## MODEL SPECIFICATIONS

<b>HEAD</b>	Multi row spraying head with air assist diffusers and twin spray nozzles. Each air diffuser features swivel adjustment and air deflector. Poly air tubes shaped to surround canopy. Left and right arms have independent hydraulic fold with manual width and height adjustment (2 sets of tractor remotes required).	<b>FLUSH TANK</b>	205L polytuff tank with top fill. Used to flush pump, filter, spray lines and nozzles.			
<b>PUMP</b>	Silvan oil-backed diaphragm type with nitrile diaphragms with brass heads and manifolds. IDS2001: 182L/min. capacity 5000kPa pressure.	<b>HAND WASH TANK</b>	15L polytuff tank with top fill.			
<b>FAN SIZE</b>	500mm twin impeller turbine fan. Power consumed 48 kw/64HP.	<b>CHEM INDUCTION</b>	Venturi suction probe.			
<b>NOZZLES</b>	Twin hollow cone ceramic nozzles per outlet with individual metering on/off non-drip taps.	<b>FRAME</b>	Galvanised steel chassis, heavy duty stand & adjustable drawbar.			
<b>GEARBOX</b>	2-speed with neutral position, oil-bath type.	<b>AGITATION</b>	Pump bypass plus venturi agitator.			
<b>CONTROLS</b>	40 Bar electric section valves, master valve, electric pressure regulator and in cab controls.	<b>PRESSURE GAUGE</b>	Glycerine filled gauge located on the valve bank.			
<b>MAIN TANK</b>	3400L Polytuff impact resistant polyethylene construction, calibrated sightline, flip top lid, 50mm camlock bottom fill.	<b>FILTRATION</b>	Suction line filter and pressure filter.			
		<b>WHEEL EQUIPMENT</b>	Tandem independent suspension with 10 x 15" tyres.			
		<b>PTO DRIVESHAFT</b>	Quality Bondioli & Pavesi constant velocity (wide angle) driveshaft with quick release pins & safety cover.			
		<b>HP REQUIRED</b>	Minimum 75 PTO HP.			
		<b>DIMENSIONS</b>	<b>L (MM)</b>	<b>W (MM)</b>	<b>H (MM)</b>	<b>KG (DRY)</b>
		<b>TG64NF5I2</b>	3995	less head 1755 folded 2470	3300	1500
		Length measured with drawbar in shortest position.				

MODEL DESCRIPTION	CODE
2 ROW 3000L TGS: IDS2001 pump, electric valve controls, 500mm twin turbine fan	TG64NF5I2
3 ROW 3000L TGS: IDS2001 pump, electric valve controls, 500mm twin turbine fan	TG64NM5I3
FACTORY OPTIONS	CODE
IDS2600 pump, 249L/min capacity, 5000kPa pressure	D99-149
Bravo 180S automatic rate controller	D99-143
Vertical lift head assembly (1 extra set of tractor remotes required)	TGS-LIFT
Quick turning hitch	D99-170
Twin galvanised snorkel	D99-172
Hydraulic row width adjustment	-
Road kit	D99-151
Over row work lights	D99-152