

Turbowrap & Tri Wrap Turbomiser



Vineyards



Pictured: 3500L Tri-Wrap

MODEL SPECIFICATIONS

HEAD	Two row spraying head: 28 venturi air shear adjustable nozzles with individual metering and on/off taps. Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms are independent hydraulic folding with adjustable width & centre frame. Boom frame is galvanised.	FRAME	Galvanised steel chassis, adjustable drawbar with jockey wheel.			
	PUMP	Stainless steel, hydraulic drive centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal.	AGITATION	Venturi agitator.		
FAN SIZE	P55DSE: 550mm dia. turbine fan, 3700 rpm. Power consumed 50 kw / 67HP.	FILTRATION	Lid strainer and large capacity suction filter.			
NOZZLES	Air shear.	WHEEL EQUIPMENT	Tandem simplicity suspension with 10 x 15" tyres (2000L) or 11.5 x 15.3" tyres (3500L).			
GEARBOX	Multiplication type through multi-grip, multi-vee belt and pulley, over-run free wheeling hub and oil bath fan housing.	PTO DRIVESHAFT	Quality Bondioli & Pavesi constant velocity (wide angle) driveshaft with quick release pins & safety cover.			
CONTROLS	Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge.	HP REQUIRED	70 PTO HP (2 row), 90 PTO HP (3 row).			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, flip top easy open lid, 50mm camlock bottom fill and 40L fresh water tank.	DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		GTU28CB5S2	4600	less head 1800 folded 2600	3300	990
		GTU38CB5S2	4975	less head 1800 folded 2800	3300	1100
		Length measured with drawbar in shortest position.				

MODEL DESCRIPTION	CODE
2000L P55DSE TRAILED 2 ROW TURBOWRAP: Includes sprayheads, P55DSE fan, hydraulic drive stainless steel pump, automatic spray rate controller, wide angle shaft, tandem suspension axle	GTU28CB5S2
3500L P55DSE TRAILED 2 ROW TURBOWRAP: Includes sprayheads, P55DSE fan, hydraulic drive stainless steel pump, automatic spray rate controller, wide angle shaft, tandem suspension axle	GTU38CB5S2
2000L P55DSE TRAILED 3 ROW TRI-WRAP: Includes sprayheads, P55DSE fan, hydraulic drive stainless steel pump, automatic spray rate controller, wide angle shaft, tandem suspension axle	GTU28CB5S3
3500L P55DSE TRAILED 3 ROW TRI-WRAP: Includes sprayheads, P55DSE fan, hydraulic drive stainless steel pump, automatic spray rate controller, wide angle shaft, tandem suspension axle	GTU38CB5S3
FACTORY OPTIONS	CODE
Quick turning hitch	D99-170
Hydraulic row width/height adjustment	-
Bravo 180S spray rate controller with hydraulic controls (in lieu)	J99-180

When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options.