

3000L Turbowrap & Tri Wrap Turbomiser



Vineyards



Pictured: 3000L Tri Wrap

MODEL SPECIFICATIONS

HEAD	Two row spraying head: 28 venturi air shear nozzles with individual metering and on/off taps. Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms have independent hydraulic folding with adjustable width & centre frame. Boom frame is fully galvanised.	HAND WASH TANK	15L polytuff tank with top fill.				
PUMP	Stainless steel hydraulic centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal.	CHEM INDUCTION	Venturi suction probe.				
FAN SIZE	500mm twin impeller turbine fan. Power cons. 48 kw/64HP.	FRAME	Galvanised steel chassis, heavy duty stand and adjustable drawbar.				
NOZZLES	Air shear.	AGITATION	Venturi agitator.				
GEARBOX	2-speed with neutral position, oil-bath type.	PRESSURE GAUGE	Glycerine filled gauge located on the valve bank.				
CONTROLS	Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge.	FILTRATION	Suction line filter and pressure filter.				
MAIN TANK	3400L Polytuff impact resistant polyethylene construction, calibrated sightline, flip top lid, 50mm camlock bottom fill.	WHEEL EQUIPMENT	Tandem independent suspension with 10 x 15" tyres.				
FLUSH TANK	205L Polytuff tank with top fill. Used to flush pump, filter, spray lines and nozzles.	PTO DRIVESHAFT	Quality Bondioli & Pavesi constant velocity (wide angle) driveshaft with quick release pins & safety cover.				
		HP REQUIRED	Minimum 75 PTO HP.				
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)	
		TU68NB512	3995	less head	1755	3300	1500
				folded	2470		
Length measured with drawbar in shortest position.							

MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
3000L TRAILED TURBOWRAP - 2 ROW: Includes sprayheads, twin fan, hydraulic drive stainless steel pump, automatic rate controller, wide angle shaft, tandem suspension axle	TU68NB512
3000L TRAILED TRI WRAP - 3 ROW: Includes sprayheads, twin fan, hydraulic drive stainless steel pump, automatic rate controller, wide angle shaft, tandem suspension axle	TU68NB513

FACTORY OPTION

FACTORY OPTION	CODE
Quick turning hitch	D99-170
Hydraulic row width/height adjustment	-
Bravo 180S spray rate controller with hydraulic controls (in lieu)	J99-180
Twin galvanised snorkel	D99-172
Road kit	D99-151
Over row work lights	D99-152

When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options.