

G2 Turbowrap & Tri Wrap Turbomiser



Vineyards



Pictured: 4000L G2 Tri Wrap

MODEL SPECIFICATIONS

HEAD	Two row spraying head: 28 venturi air shear nozzles with individual metering and on/off taps. Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms have independent hydraulic folding with adjustable width & centre frame. Boom frame is fully galvanised.	MIXER TANK	Chemical mixer hopper with tap controls for rinse, venturi and main tank rinse. Venturi transfer to main tank.				
PUMP	Stainless steel, hydraulic drive centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal.	FRAME	Galvanised steel chassis, adjustable drawbar & heavy duty stand.				
FAN SIZE	500mm twin impeller turbine fan. Power consumed 48 kw/64HP.	AGITATION	Twin venturi agitators.				
NOZZLES	Air shear.	PRESSURE GAUGE	Glycerine filled gauge located on valve bank.				
GEARBOX	2-speed with neutral position, oil-bath type.	FILTRATION	Suction line filter and pressure filter.				
CONTROLS	Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge.	WHEEL EQUIPMENT	2000L: Tandem simplicity suspension with 10 x 15" tyres. 4000L: Tandem simplicity suspension with 11.5 x 15.3" tyres.				
MAIN TANK	Polytuff impact resistant polyethylene construction with calibrated sightline and 50mm camlock top and bottom fill.	PTO DRIVESHAFT	Quality Bondioli & Pavesi constant velocity (wide angle) driveshaft with quick release pins & safety cover.				
FLUSH TANK	Polytuff tank with top fill. Used to flush pump, filter, spray lines and nozzles.	HP REQUIRED	75 PTO HP (2 row Turbowrap), 90 PTO HP (3 row Tri-Wrap).				
HAND WASH TANK	Polytuff tank filled through cap. Tap located next to Chemical mixer tank hopper.	DIMENSIONS	L (mm)	W (mm)	H (mm)	KG (dry)	
		TU28NB5S2	5205	less head	1820	3300	1800
				folded	2600		
		TU48NB5S2	5730	less head	1950	3300	2000
				folded	2800		
Length measured with drawbar in shortest position.							

MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
2000L G2 TRAILED TURBOWRAP - 2 ROW: Includes sprayheads, twin fan, hydraulic drive stainless steel pump, automatic rate controller, wide angle shaft, tandem suspension axle	TU28NB5S2
4000L G2 TRAILED TURBOWRAP - 2 ROW: Includes sprayheads, twin fan, hydraulic drive stainless steel pump, automatic rate controller, wide angle shaft, tandem suspension axle	TU48NB6S2
2000L G2 TRAILED TRI-WRAP - 3 ROW: Includes sprayheads, twin fan, hydraulic drive stainless steel pump, automatic rate controller, wide angle shaft, tandem suspension axle	TU28NB5S3
4000L G2 TRAILED TRI-WRAP - 3 ROW: Includes sprayheads, twin fan, hydraulic drive stainless steel pump, automatic spray rate controller, wide angle shaft, tandem suspension axle	TU48NB6S3

FACTORY OPTION

FACTORY OPTION	CODE
Quick turning hitch	D99-170
Hydraulic row width/height adjustment	-
Bravo 180S spray rate controller with hydraulic controls (in lieu)	J99-180
Twin galvanised snorkel	D99-172
Road kit	D99-151
Over row work lights	D99-152

When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options.