

4000L Turbo SCRAM Turbowrap & Tri Wrap



Pictured: 2000L 2 Row Turbo SCRAM

MODEL SPECIFICATIONS

| | | | | | | | |
|--------------------------|--|-------------------------------------|---|---------------|---------------|-----------------|------|
| HEAD | Two row spraying head: 28 venturi air shear adjustable nozzles with individual metering and on/off taps. Three row spraying head: 42 venturi air shear adjustable nozzles with individual metering and on/off taps. Left & right arms are independent hydraulic folding with adjustable width & centre frame. Boom frame is galvanised. | TANK | Polytuff impact resistant polyethylene construction, calibrated sight line, flip top easy open lid, 50mm camlock bottom fill and hand wash tank. (G2 fitted with flush tank and chemical mixer hopper) | | | | |
| PUMP | Stainless steel, hydraulic drive centrifugal pump, 350 L/min. Stainless steel shaft and Viton/ceramic seal. Driven by tractor remotes. | FRAME | Galvanised steel chassis, linkage hitch fitted with hydraulic power pack. | | | | |
| FANS | 320 mm turbine fan, one per air tube, 3600 rpm. Power consumed 29 kw / 38HP. | AGITATION | Venturi agitator. | | | | |
| HYDRAULIC CONTROL | Hitch mounted hydraulic power pack with; 40L oil reservoir with cartridge particulate filter, motors fitted with case drain, hydraulic distribution block incorporates anti-cavitation and pressure relief valves, 12V oil cooler. | FILTRATION | Lid strainer and large capacity suction filter. | | | | |
| NOZZLES | Air shear. | WHEEL EQUIPMENT | Tandem simplicity suspension axle with 11.5 x 15.3" tyres. | | | | |
| CONTROLS | Electric section valves with Bravo 180S automatic rate controller. Large 100mm pressure gauge. | PTO DRIVESHAFT | Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover. | | | | |
| | | HP REQUIRED | Minimum 65 PTO HP (2 row), 80 PTO HP (3 row) | | | | |
| | | DIMENSIONS | L (MM) | W (MM) | H (MM) | KG (DRY) | |
| | | SETU48HB6S2 | 5230 | less head | 1950 | 3300 | 1820 |
| | | | | folded | 2800 | | |
| | | STU48HB6S2 | 5730 | less head | 1950 | 3300 | 2000 |
| | | | | folded | 2800 | | |
| | | Length measured with linkage hitch. | | | | | |

| MODEL DESCRIPTION | CODE |
|---|-------------|
| 4000L G2E TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads 4 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle | SETU48HB6S2 |
| 4000L G2 TURBO SCRAM TRAILED 2 ROW TURBOWRAP: Includes sprayheads 4 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle | STU48HB6S2 |
| 4000L G2E TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads 6 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system tandem suspension axle | SETU48HB6S3 |
| 4000L G2 TURBO SCRAM TRAILED 3 ROW TRI-WRAP: Includes sprayheads 6 x 320mm fans, Hydraulic drive stainless steel pump, automatic spray rate controller, self contained hydraulic drive system, tandem suspension axle | STU48HB6S3 |
| FACTORY OPTIONS | CODE |
| Bravo 180S spray rate controller with hydraulic controls (in lieu) | J99-180 |
| Hydraulic row width/height adjustment | - |
| Hydraulic pump driven through power pack | D99-185 |
| 100L Flush Tank (to suit G2E) | J99-112 |
| When ordering hydraulic drive pumps, tractor hydraulic capacity and system must be written on order. Note: Not all options will fit all models. Extra charges may apply to fitment of some options. | |