

Casotti - Linkage Sprayer



Pictured: 600L Casotti

MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. APS71: 71L/min. capacity 4000kPa pressure.	AGITATION	Bypass agitation.			
CASOTTI MOTOR	An electric 12 volt motor is connected to the tractor battery which powers the oscillating movement of the nozzle arms. The arms swing 180°. This movement is symmetrical to the tractor's passage.	SPRAY JETS	3 oscillating high pressure jets (20 bar) Up to 12m spray coverage.			
CONTROLS	2 outlet brass manual control valve with pressure regulator. Mounted forward for easy access.	PRESSURE GAUGE	0-60 Bar dual stage glycerine filled gauge.			
TANK	Low profile 600/800/1100L Polyuff impact resistant polyethylene construction, external sightline with floating ball and non-spill offset screw-down lid with single breather. 15L freshwater tank with screw-down lid and on/off tap. 4L toolbox with polythylene lid. 50mm Camlock bottom fill (1100L only).	FILTRATION	Lid strainer, suction line strainer with stop valve fitted at side of tank to enable ease of filter maintenance.			
FRAME	Fully galvanised steel, cat II linkage.	PTO DRIVESHAFT	Quality driveshaft with quick release pins & safety cover.			
		DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
		K06N-71WG (LESS KIT)	1025	1150	1300	105
		K08N-71WG (LESS KIT)	1350	1395	1315	145
		K11N-71WG (LESS KIT)	1350	1395	1610	160

MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
600L LINKAGE CASOTTI SPRAYER: APS71 pump, Casotti kit	K06N-71WG
800L LINKAGE CASOTTI SPRAYER: APS71 pump, Casotti kit	K08N-71WG
1100L LINKAGE CASOTTI SPRAYER: APS71 pump, Casotti kit	K11N-71WG
CASOTTI KIT: With mounting brackets and hydraulic hoses	K99-36