

Trailed Economy Pasture Sprayer



Pictured: 1000L Economy Pasture sprayer with optional electric controls and undervine boom.

MODEL SPECIFICATIONS

PUMP	Silvan self-priming oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. BP60/20: 58L/min capacity 2000kPa pressure. BP125/20: 121L/min. capacity 2000kPa pressure	PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge mounted on adjustable arm.			
		FILTRATION	Lid strainer and suction line strainer			
CONTROLS	One lever 3 outlet control with pressure regulator mounted on adjustable arm.	WHEELS	60mm straight single axle fitted with 15" tubeless tyres on galvanised rims (max speed rating 30km/h).			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, non-spill screw-down lid with dual breathers.	PTO	Quality driveshaft with quick release pins & safety cover.			
FRAME	Galvanised RHS steel construction, jockey wheel & height adjustable tow hitch.	DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
AGITATION	Bypass action.	J10-S60	1400	2600	1620	290
		J20-S105	1550	3500	2100	440

MODEL DESCRIPTION	CODE
1000L PASTURE SPRAYER: BP60/20 diaphragm pump manual controls on pump.	J10-S60
2000L PASTURE SPRAYER: BP125/20 diaphragm pump manual controls on pump.	J20-S105
FACTORY OPTIONS	CODE
6m Field boom	032-044-6
6m Devil boom with hydraulic fold	032-19D
8m Field boom	032-044-8
8m Devil boom with hydraulic fold	032-25D
10m Field boom	032-014-10
10m Devil boom with hydraulic fold	032-32DM
6, 8 and 10m Devil boom hydraulic lift	032-19DL
Undervine and mid row boom	032-HERB
16L foam marker (double sided)	K99-39
Economy hosereel, 20m hose (10mm ID) and Triam spraygun	180E02012CT
Electric valve controls with pressure regulator and in cab pressure adjustment	K99-29
Bravo 180S automatic rate controller	J99-151
BP125/20, 121L/min capacity, 2000kPa driven by 5.5HP Honda	CUSH-14

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.