

Trailed Turf Sprayer



Pictured: Trailed Turf Sprayer with optional 8m Devil boom and foam marker

MODEL SPECIFICATIONS

PUMP	Silvan self-priming, oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised body. Direct coupled to 6.5HP Honda motor. BP125/20: 121L/min. capacity 2000 kPa.	PRESSURE GAUGE	0-25 Bar dual stage glycerine filled gauge.		
CONTROLS	3 outlet control with pressure regulator mounted on pump. Pressure gauge on control unit.	FILTRATION	Suction line filter & lid strainer.		
TANK	1000/2000L polytuff impact resistant polyethylene construction. Calibrated sight line. Non-spill screw-down lid with breather.	WHEELS	Tubeless 29 x 13.5 - 15" turf tyres with galvanised rims on 1000L unit. Tubeless 31 x 13.5 - 15" turf tyres with galvanised rims on 2000L unit.		
FRAME	Galvanised RHS steel construction with jockey wheel.	HOSEREEL	30m of 19mm PVC hose and fish mouth fertiliser nozzle.		
AGITATION	Bypass action and venturi agitator.	DIMENSIONS	L (MM)	W (MM)	H (MM)
		PR10-01	3400	1870	1825
		PR20-2	3500	1550	2100
					KG (DRY)
					275
					400

MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
1000L TURF SPRAYER: BP125/20 diaphragm pump, direct coupled to 6.5HP Honda motor, manual controls on pump and Pitarm hosereel with fish mouth nozzle.	PR10-01
2000L TURF SPRAYER: BP125/20 diaphragm pump, direct coupled to 6.5HP Honda motor, manual controls on pump and Pitarm hosereel with fish mouth nozzle.	PR20-2

FACTORY OPTIONS

FACTORY OPTIONS	CODE
6m Field boom	032-044-6
6m Devil boom with hydraulic fold	032-19D
8m Field boom	032-044-8
8m Devil boom with hydraulic fold	032-25D
10m Field boom	032-014-10
10m Devil boom with hydraulic fold	032-32DM
6, 8 and 10m Devil boom hydraulic lift	032-19DL
16L foam marker (double sided)	K99-39
Electric valve controls with pressure regulator and in cab pressure adjustment	K99-29
Bravo 180S automatic rate controller	J99-151

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.