

# Linkage Suntuff



Vineyards



Orchards



Pictured: 400L Suntuff

## MODEL SPECIFICATIONS

<b>PUMP</b>	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body. APS71: 67L/min. capacity 5000kPa pressure APS96: 88L/min. capacity 5000kPa pressure.	<b>TANK</b>	Polytuff, impact resistant, polyethylene construction with litre calibrations, non-spill screw-down lid.			
<b>FAN SIZE</b>	Axial flow type, fan with curved nylon reinforced blades, galvanised cowling and protective mesh cover. 600mm with 8 blades on 200L unit 700mm with 8 blades on 400L unit 800mm with 10 blades on 500L unit	<b>FRAME</b>	Galvanised steel, suit cat I & II linkage (200L cat I linkage only)			
<b>NOZZLES</b>	Flip-over type for dilute/concentrate spraying, ceramic jets, stainless steel swirl-plates. 200L unit: 10 nozzles (5 per side) twist on/off 400L unit: 12 flip over nozzles (6 per side) twist on/off 500L unit: 14 flip over nozzles (7 per side) twist on/off	<b>AGITATION</b>	200L: bypass, 400L / 500L: dual bypass			
<b>GEARBOX</b>	Single-speed with neutral position, oil-bath type.	<b>PRESSURE GAUGE</b>	Glycerine filled gauge, located on the control valve.			
<b>CONTROLS</b>	3 outlet with pressure regulator. 400/500L models standard with extra length hoses - for tractor control mount.	<b>FILTRATION</b>	Lid strainer, suction line strainer and stainless steel nozzle filters.			
		<b>PTO DRIVESHAFT</b>	Quality driveshaft with quick release pins & safety cover.			
		<b>HP REQUIRED</b>	200/400L: Minimum 25 PTO HP, 500L: Minimum 40 PTO HP.			
		<b>DIMENSIONS</b>	<b>L (MM)</b>	<b>W (MM)</b>	<b>H (MM)</b>	<b>KG (DRY)</b>
		<b>D026-71</b>	1070	1000	1060	90
		<b>D047-71</b>	1330	1190	1200	134
		<b>D058-96</b>	1400	1190	1325	140

## MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
SUNTUFF 200L: APS71 Pump, 600mm fan	D026-71
SUNTUFF 400L: APS71 Pump, 700mm fan	D047-71
SUNTUFF 500L: APS96 Pump, 800mm fan	D058-96
SUNTUFF 500L: APS96 Pump, 800mm fan, electric controls	D058-96E

## DEALER FITMENT OPTIONS

DEALER FITMENT OPTIONS	FAN SIZE (MM)	CODE
One - sided conveyor	800	D99-99
Two - sided deflector	600	D99-98
Two - sided deflector	700	D99-92B
Two - sided conveyor	700	D99-177
Two - sided deflector	800	D99-100
Bottom air deflectors	600/700/800	D99-63

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.