

Oktopus Sprayer



Vineyards



Berries



Pictured: 2000L Oktopus

MODEL SPECIFICATIONS

PUMP	Silvan oil-backed diaphragm type with nitrile diaphragms, corrosion resistant, cast anodised aluminium body. APS96: 88L/min. capacity, 5000kPa pressure APS121:115L/min capacity, 5000kPa pressure.			
FAN SIZE	450mm diameter turbine fan, 10 fishtail outlets.			
NOZZLES	Flip-over type for dilute/concentrate spraying with ceramic hollow cone nozzles and 10 nozzles (5 per side) twist on/off.			
GEARBOX	Two speed with neutral position, oil-bath type.			
CONTROLS	40 bar electric section valves, master valve, electric pressure regulator and in cab controls.			
TANK	Polytuff impact resistant polyethylene construction, calibrated sight line, non-spill lid. 40 litre fresh water tank fitted to 2000L unit.			
FRAME	500L: Galvanised steel, suit cat I & II linkage 2000L: Galvanised steel with jockey wheel & adjustable drawbar.			
AGITATION	500L: Dual bypass. 2000L: Pump bypass plus venturi agitator.			
PRESSURE GAUGE	100mm, 0-60 bar glycerine filled gauge with bar increments.			
FILTRATION	Lid strainer, suction line strainer and stainless steel nozzle filters.			
2000L WHEEL EQUIPMENT	Glideflex suspension axle, 2 x 15" tubeless tyres on galvanised rims (max speed rating 30 km/h).			
PTO DRIVESHAFT	Quality driveshaft with quick release pins and safety cover.			
HP REQUIRED	Minimum 50HP.			
DIMENSIONS	L (MM)	W (MM)	H (MM)	KG (DRY)
D05SLV-96	1400	1190	2500	140
D20SLV-121EGL	3750	1540	2500	640
Length measured with drawbar in shortest position.				

MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
OKTOPUS 500L: APS96 pump, Oktopus fan, electric valve controls	D05SLV-96
OKTOPUS 2000L: APS121 pump, Oktopus fan, electric valve controls, Glideflex axle	D20SLV-121EGL

FACTORY OPTIONS

FACTORY OPTIONS	CODE
Bravo 180S automatic rate controller	D99-143
Flotation tyres - 400/60 x 15.5" with fixed axle (in lieu of standard singles)	D99-80

Extra charges may apply to fitment of some options.