

# Trailed Stiletto 2000L



Vineyards



Orchards



Pictured: 2000L Stiletto with optional flotation tyres

## MODEL SPECIFICATIONS

<b>PUMP</b>	Silvan oil-backed diaphragm type with nitrile diaphragms and corrosion resistant, cast anodised aluminium body with brass heads and manifolds. IDS1701: 161L/min. capacity 5000kPa pressure.	<b>FRAME</b>	Galvanised steel with jockey wheel & adjustable drawbar.			
	<b>FAN SIZE</b>	900mm axial flow type, 10 bladed fan with curved nylon reinforced blades, air straightening vanes and protective mesh cover.	<b>AGITATION</b>	Pump bypass plus venturi agitator.		
<b>NOZZLES</b>	Flip-over type for dilute/concentrate spraying. Ceramic jets, stainless steel swirl-plates, 16 nozzles with twist on/off.	<b>PRESSURE GAUGE</b>	100mm, 0-60 bar glycerine filled gauge with bar increments.			
<b>GEARBOX</b>	Oil-bath type, 2-speed with neutral position.	<b>FILTRATION</b>	Lid strainer, suction line strainer and stainless steel nozzle filters.			
<b>CONTROLS</b>	40 bar electric section valves, master valve, electric pressure regulator and in cab controls.	<b>WHEEL EQUIPMENT</b>	Glideflex suspension axle, 2 x 15" tubeless tyres on galvanised rims (max speed rating 30 km/h).			
<b>TANK</b>	Polytuff impact resistant polyethylene construction, calibrated sight line, easy open lid, 40mm drain valve and built-in 15L fresh water tank.	<b>PTO DRIVESHAFT</b>	Quality Bondioli & Pavesi driveshaft with quick release pins & safety cover.			
		<b>HP REQUIRED</b>	Minimum 60 PTO HP.			
		<b>DIMENSIONS</b>	<b>L (MM)</b>	<b>W (MM)</b>	<b>H (MM)</b>	<b>KG (DRY)</b>
		<b>DST23AF8G</b>	3800	1540	1500	640
		Length measured with drawbar in shortest position.				

## MODEL DESCRIPTION

MODEL DESCRIPTION	CODE
STILETTO 2000L: IDS1701 pump, 900mm fan, electric valve controls, Glideflex axle, wide angle shaft	DST23AF8G
STILETTO 2000L: IDS1701 pump, 900mm fan, Glideflex axle, wide angle shaft, Bravo 180S automatic rate controller	DST23AB8G

## FACTORY OPTIONS

FACTORY OPTIONS	CODE
Twin nozzles (includes extra nozzles)	D99-182
Flotation tyres - 400/60 x 15.5" with fixed axle (in lieu of standard singles)	D99-80

Note: Not all options will fit all models. Extra charges may apply to fitment of some options.